

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

IN THE CLAIMS:

Please amend the following claims having the same number as indicated:

1. (Canceled).
2. (Currently Amended). A method, as set forth in claim [4] 3, wherein the horizontal component of the acceleration is in a plane defined by the first and second directions.
3. (Currently Amended). A method, ~~as set forth in claim 1,~~ for establishing an acceleration of a vehicle, comprising the steps of:
establishing a gravity vector representing acceleration due to gravity;
measuring acceleration of the vehicle in a first direction and establishing a first acceleration value;
measuring acceleration of the vehicle in a second direction and establishing a second acceleration value, the first and second directions being perpendicular, and
establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values, wherein the step of establishing the first acceleration value includes the step of applying a first offset value and wherein the step of establishing the second acceleration value includes the step of applying a second offset value.
4. (Previously Presented). A method, as set forth in claim 3, including the step of establishing the first and second offset values using a calibration routine.

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

5. (Original). A method, as set forth in claim 3, the steps of measuring the acceleration of the vehicle being performed by an accelerometer device, the accelerometer device for providing first and second output signals corresponding to acceleration of the device in first and second accelerometer directions, the first and second accelerometer directions being perpendicular, the calibration routine being performed when the accelerometer device is not moving and including the steps of:

reading the first and second output signals when the accelerometer device is in a first position;

rotating the accelerometer device 180 degrees to a second position;

reading the first and second output signals when the accelerometer device is in the second position; and,

determining the first and second offset values as a function of the first and second signals read when the accelerometer device is in the first position and the first and second signals read when the accelerometer device is in the second position.

6. (Original). A method as set forth in claim 4, the first and second offset values being determined by:

$$X_0 = (X_1 + X_2) / 2, \text{ and}$$

$$Y_0 = (Y_1 + Y_2) / 2,$$

where X_0 is the first offset value, X_1 is the first output signal read when the accelerometer device is in the first position, X_2 is the first output signal read when the accelerometer device is in the second position, Y_0 is the second offset value, Y_1 is the second output signal read when the accelerometer device is in the first position, and Y_2 is the second output signal read when the accelerometer device is in the second position.

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

7. (Original). A method, as set forth in claim 4, wherein the accelerometer device is a two-axis device which consists of an integrated circuit that contains both x and y accelerometer functions.

8. (Original). A method, as set forth in claim 4, the calibration routine further including the step of calculating a scaling factor as a function of the first and second signals read when the accelerometer device is in the first position and the first and second signals read when the accelerometer device is in the second position.

9. (Original). A method, as set forth in claim 7, where the scaling factor is calculated using:

$$K = ((X_2 - X_1)^2 + (Y_2 - Y_1)^2) / 4,$$

where K is the scaling factor, X_1 is the first output signal read when the accelerometer device is in the first position, X_2 is the first output signal read when the accelerometer device is in the second position, Y_1 is the second output signal read when the accelerometer device is in the first position, and Y_2 is the second output signal read when the accelerometer device is in the second position.

10. (Original). A method, as set forth in claim 7, where the scaling factor is calculated using:

$$K = G^2, \text{ wherein } G \text{ is the magnitude of the gravity vector.}$$

11. (Currently Amended). A method, ~~as set forth in claim 1,~~ for establishing an acceleration of a vehicle, comprising the steps of:
establishing a gravity vector representing acceleration due to gravity;

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

measuring acceleration of the vehicle in a first direction and establishing a first acceleration value;

measuring acceleration of the vehicle in a second direction and establishing a second acceleration value, the first and second directions being perpendicular; and

establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values,
wherein the steps of measuring the acceleration of the vehicle being performed by an accelerometer device, the accelerometer device for providing first and second output signals representing acceleration of the device in first and second accelerometer directions, respectively, the first and second accelerometer directions being perpendicular, the step of establishing a gravity vector including the steps of:

- (a) reading the first and second output signals; and,
- (b) determining a new gravity vector as a function of a previous gravity vector the first and second output signals and a low pass filter with a predetermined time constant.

12. (Original). A method, as set forth in claim 11, the new gravity vector having first and second components, the first and second components of the new gravity vector determined by:

$$G_X = (1 - (1/A)) \cdot G_{OLD_X} + (x / A), \text{ and}$$

$$G_Y = (1 - (1/A)) \cdot G_{OLD_Y} + (y / A),$$

where G_X is the first component of the new gravity vector, A is a predetermined constant, G_{OLD_X} is a component of the previous gravity vector, G_Y is the second component of the

Applicant: William R. Kissel
 Serial No.: 10/828,756
Group Art Unit: 3682

new gravity vector, G_{OLD_Y} is a second component of the previous gravity vector, x is the measured acceleration in the first direction and y is the measured acceleration in the second direction.

13. (Original). A method, as set forth in claim 11, the time constant being about 4 milliseconds.

14. (Currently Amended). A method, as set forth in claim 1, for establishing an acceleration of a vehicle, comprising the steps of:

establishing a gravity vector representing acceleration due to gravity;

measuring acceleration of the vehicle in a first direction and establishing a first acceleration value;

measuring acceleration of the vehicle in a second direction and establishing a second acceleration value, the first and second directions being perpendicular; and,

establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values,

wherein the horizontal component of the acceleration is determined by:

$D = |G \times R| / (G)$, where D is the horizontal component of the acceleration, G is the gravity vector, R is measured acceleration during a braking event, and G is the magnitude of the gravity vector.

15. (Currently Amended). A method, as set forth in claim 1, for establishing an acceleration of a vehicle, comprising the steps of:

establishing a gravity vector representing acceleration due to gravity;

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

measuring acceleration of the vehicle in a first direction and establishing a first acceleration value;

measuring acceleration of the vehicle in a second direction and establishing a second acceleration value, the first and second directions being perpendicular; and,

establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values,
wherein the horizontal component of the acceleration is determined by:

$D = | \mathbf{G} \times \mathbf{R} | / (G^2)$, where D is the horizontal component of the acceleration, G is the gravity vector, R is measured acceleration during a braking event, and G is the magnitude of the gravity vector.

16. (Currently Amended). A method, ~~as set forth in claim 1,~~ for establishing an acceleration of a vehicle, comprising the steps of:

establishing a gravity vector representing acceleration due to gravity;

measuring acceleration of the vehicle in a first direction and establishing a first acceleration value;

measuring acceleration of the vehicle in a second direction and establishing a second acceleration value, the first and second directions being perpendicular; and,

establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values,
wherein the horizontal component of the acceleration is determined by:

Applicant: William R. Kissel
 Serial No.: 10/828,756
 Group Art Unit: 3682

$D = |((Y_D \bullet X_G) - (X_D \bullet Y_G) / (G))|$, where D is the absolute value of the magnitude of the horizontal component of the acceleration, X_D is the measured acceleration in the first direction, Y_D is the measured acceleration in the second direction, X_G is a first component of the gravity vector, Y_G is a second component of the gravity vector, and G is the magnitude of the gravity vector.

17. (Currently Amended). A method, ~~as set forth in claim 1,~~ for establishing an acceleration of a vehicle, comprising the steps of:

establishing a gravity vector representing acceleration due to gravity;

measuring acceleration of the vehicle in a first direction and establishing a first acceleration value;

measuring acceleration of the vehicle in a second direction and establishing a second acceleration value, the first and second directions being perpendicular; and,

establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values,

wherein the horizontal component of the acceleration is determined by:

$D = |((Y_D \bullet X_G) - (X_D \bullet Y_G) / (G^2))|$, where D is the absolute value of the magnitude of the horizontal component of the acceleration, X_D is the measured acceleration in the first direction, Y_D is the measured acceleration in the second direction, X_G is a first component of the gravity vector, Y_G is a second component of the gravity vector, and G is the magnitude of the gravity vector.

18. (Currently Amended). A method, ~~as set forth in claim 1,~~ for establishing an acceleration of a vehicle, comprising the steps of:

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

establishing a gravity vector representing acceleration due to gravity;

measuring acceleration of the vehicle in a first direction and establishing a first acceleration value;

measuring acceleration of the vehicle in a second direction and establishing a second acceleration value, the first and second directions being perpendicular; and,

establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values,
wherein the horizontal component of the acceleration is determined by:

$$D = ((Y_D \bullet X_G) - (X_D \bullet Y_G)) / (G),$$
 where D is the horizontal component of the acceleration, X_D is the measured acceleration in the first direction, Y_D is the measured acceleration in the second direction, X_G is a first component of the gravity vector, Y_G is a second component of the gravity vector, and G is the magnitude of the gravity vector.

19. (Currently Amended). A method, ~~as set forth in claim 1,~~ for establishing an acceleration of a vehicle, comprising the steps of:

establishing a gravity vector representing acceleration due to gravity;

measuring acceleration of the vehicle in a first direction and establishing a first acceleration value;

measuring acceleration of the vehicle in a second direction and establishing a second acceleration value, the first and second directions being perpendicular; and,

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values,
wherein the horizontal component of the acceleration is determined by:

$D = ((Y_D \bullet X_G) - (X_D \bullet Y_G) / (G^2))$, where D is the horizontal component of the acceleration, X_D is the measured acceleration in the first direction, Y_D is the measured acceleration in the second direction, X_G is a first component of the gravity vector, Y_G is a second component of the gravity vector, and G is the magnitude of the gravity vector.

20. (Canceled).

21. (Currently Amended). A system, as set forth in claim [20] 22, wherein the horizontal component of the acceleration is in a plane defined by the first and second directions.

22. (Currently Amended). A system, ~~as set forth in claim 20~~, for establishing an acceleration of a vehicle, comprising:

an accelerometer device for measuring acceleration of the vehicle in a first direction and responsively establishing a first acceleration value and for measuring acceleration of the vehicle in a second direction and responsively establishing a second acceleration value, the first and second directions being perpendicular; and,

a controller coupled to the accelerometer device for establishing a gravity vector representing acceleration due to gravity and for establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values, the controller for applying a first offset to the

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

measured acceleration of the vehicle in the first direction and for applying a second offset to the measured acceleration of the vehicle in the second direction.

23. (Original). A system, as set forth in claim 22, the controller for determining the first and second offset values using a calibration routine.

24. (Original). A system, as set forth in claim 23, the controller for performing the calibration routine while the accelerometer device is not moving, the calibration routine including the steps of reading the first and second output signals when the accelerometer device is in a first position, rotating the accelerometer device 180 degrees to a second position, reading the first and second output signals when the accelerometer device is in the second position, and determining the first and second offset values as a function of the first and second signals read when the accelerometer device is in the first position and the first and second signals read when the accelerometer device is in the second position.

25. (Original). A system, as set forth in claim 22, the first and second offset values being determined by:

$$X_0 = (X_1 + X_2) / 2, \text{ and}$$

$$Y_0 = (Y_1 + Y_2) / 2,$$

where X_0 is the first offset value, X_1 is the first output signal read when the accelerometer device is in the first position, X_2 is the first output signal read when the accelerometer device is in the second position, Y_0 is the second offset value, Y_1 is the second output signal read when the accelerometer device is in the first position, and Y_2 is the second output signal read when the accelerometer device is in the second position.

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

26. (Original). A system, as set forth in claim 24, wherein the accelerometer device is a two-axis device which consists of an integrated circuit that contains both x and y accelerometer functions.

27. (Original). A system, as set forth in claim 26, the calibration routine further including the step of calculating a scaling factor as a function of the first and second signals read when the accelerometer device is in the first position and the first and second signals read when the accelerometer device is in the second position.

28. (Original). A system, as set forth in claim 26, where the scaling factor is calculated using:

$$K = ((X_2 - X_1)^2 + (Y_2 - Y_1)^2) / 4,$$

where K is the scaling factor, X_1 is the first output signal read when the accelerometer device is in the first position, X_2 is the first output signal read when the accelerometer device is in the second position, Y_1 is the second output signal read when the accelerometer device is in the first position, and Y_2 is the second output signal read when the accelerometer device is in the second position

29. (Original). A system, as set forth in claim 22, where the scaling factor is calculated using:

$$K = G^2,$$

where K is the scaling factor, and G is the magnitude of the gravity vector.

30. (Currently Amended). A system, ~~as set forth in claim 20, for establishing~~ an acceleration of a vehicle, comprising:

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

an accelerometer device for measuring acceleration of the vehicle in a first direction and responsively establishing a first acceleration value and for measuring acceleration of the vehicle in a second direction and responsively establishing a second acceleration value, the first and second directions being perpendicular; and,

a controller coupled to the accelerometer device for establishing a gravity vector representing acceleration due to gravity and for establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values, the controller establishing the gravity vector by (a) reading the first and second output signals, and (b) determining a new gravity vector as a function of a previous gravity vector, the first and second output signals, and a low pass filter with a second predetermined time constant.

31. (Original). A system, as set forth in claim 30, the new gravity vector having first and second components, the first and second components of the new gravity vector determined by:

$$G_X = (1 - (1/A)) \cdot G_{OLD_X} + (x/A), \text{ and}$$

$$G_Y = (1 - (1/A)) \cdot G_{OLD_Y} + (y/A),$$

where G_X is the first component of the new gravity vector, A is a predetermined constant, G_{OLD_X} is a component of the previous gravity vector, G_Y is the second component of the new gravity vector, G_{OLD_Y} is a second component of the previous gravity vector, x is the measured acceleration in the first direction and y is the measured acceleration in the second direction.

32. (Original). A system, as set forth in claim 30, the predetermined time constant being about 4 milliseconds.

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

33. (Original). A system, ~~as set forth in claim 20,~~ for establishing an acceleration of a vehicle, comprising:

an accelerometer device for measuring acceleration of the vehicle in a first direction and responsively establishing a first acceleration value and for measuring acceleration of the vehicle in a second direction and responsively establishing a second acceleration value, the first and second directions being perpendicular; and,

a controller coupled to the accelerometer device for establishing a gravity vector representing acceleration due to gravity and for establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values, wherein the horizontal component of the acceleration is determined by:

$D = |G \times R| / (G)$, where D is the horizontal component of the acceleration, G is the gravity vector, R is measured acceleration during a braking event, G x R is the cross product of vectors G and R, and G is the magnitude of the gravity vector.

34. (Currently Amended). A system, ~~as set forth in claim 20,~~ for establishing an acceleration of a vehicle, comprising:

an accelerometer device for measuring acceleration of the vehicle in a first direction and responsively establishing a first acceleration value and for measuring acceleration of the vehicle in a second direction and responsively establishing a second acceleration value, the first and second directions being perpendicular; and,

a controller coupled to the accelerometer device for establishing a gravity vector representing acceleration due to gravity and for establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector

Applicant: William R. Kissel
 Serial No.: 10/828,756
 Group Art Unit: 3682

and the first and second acceleration values, wherein the horizontal component of the acceleration is determined by:

$D = |G \times R| / (G^2)$, where D is the horizontal component of the acceleration, G is the gravity vector, R is measured acceleration during a braking event, and G is the magnitude of the gravity vector.

35. (Currently Amended). A system, ~~as set forth in claim 20,~~ for establishing an acceleration of a vehicle, comprising:

an accelerometer device for measuring acceleration of the vehicle in a first direction and responsively establishing a first acceleration value and for measuring acceleration of the vehicle in a second direction and responsively establishing a second acceleration value, the first and second directions being perpendicular; and,

a controller coupled to the accelerometer device for establishing a gravity vector representing acceleration due to gravity and for establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values, wherein the horizontal component of the acceleration is determined by:

$D = |(Y_D \bullet X_G) - (X_D \bullet Y_G) / (G)|$, where D is the absolute value of the magnitude of the horizontal component of the acceleration, X_D is the measured acceleration in the first direction, Y_D is the measured acceleration in the second direction, X_G is a first component of the gravity vector, Y_G is a second component of the gravity vector, and G is the magnitude of the gravity vector.

36. (Currently Amended). A system, ~~as set forth in claim 20,~~ for establishing an acceleration of a vehicle, comprising:

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

an accelerometer device for measuring acceleration of the vehicle in a first direction and responsively establishing a first acceleration value and for measuring acceleration of the vehicle in a second direction and responsively establishing a second acceleration value, the first and second directions being perpendicular; and,

a controller coupled to the accelerometer device for establishing a gravity vector representing acceleration due to gravity and for establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values, wherein the horizontal component of the acceleration is determined by:

$$D = |[(Y_D \bullet X_G) - (X_D \bullet Y_G) / (G^2)]|$$
, where D is the absolute value of the magnitude of the horizontal component of the acceleration, X_D is the measured acceleration in the first direction, Y_D is the measured acceleration in the second direction, X_G is a first component of the gravity vector, Y_G is a second component of the gravity vector, and G is the magnitude of the gravity vector.

37. (Currently Amended). A system, ~~as set forth in claim 20,~~ for establishing an acceleration of a vehicle, comprising:

an accelerometer device for measuring acceleration of the vehicle in a first direction and responsively establishing a first acceleration value and for measuring acceleration of the vehicle in a second direction and responsively establishing a second acceleration value, the first and second directions being perpendicular; and,

a controller coupled to the accelerometer device for establishing a gravity vector representing acceleration due to gravity and for establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector

Applicant: William R. Kissel
 Serial No.: 10/828,756
Group Art Unit: 3682

and the first and second acceleration values, wherein the horizontal component of the acceleration is determined by:

$D = ((Y_D \bullet X_G) - (X_D \bullet Y_G)) / (G)$, where D is the horizontal component of the acceleration, X_D is the measured acceleration in the first direction, Y_D is the measured acceleration in the second direction, X_G is a first component of the gravity vector, Y_G is a second component of the gravity vector, and G is the magnitude of the gravity vector.

38. (Currently Amended). A system, ~~as set forth in claim 20,~~ for establishing an acceleration of a vehicle, comprising:

an accelerometer device for measuring acceleration of the vehicle in a first direction and responsively establishing a first acceleration value and for measuring acceleration of the vehicle in a second direction and responsively establishing a second acceleration value, the first and second directions being perpendicular; and,

a controller coupled to the accelerometer device for establishing a gravity vector representing acceleration due to gravity and for establishing a magnitude of a horizontal component of the acceleration of the vehicle as a function of the gravity vector and the first and second acceleration values, wherein the horizontal component of the acceleration is determined by:

$D = ((Y_D \bullet X_G) - (X_D \bullet Y_G)) / (G^2)$, where D is the horizontal component of the acceleration, X_D is the measured acceleration in the first direction, Y_D is the measured acceleration in the second direction, X_G is a first component of the gravity vector, Y_G is a second component of the gravity vector, and G is the magnitude of the gravity vector.

39. (Canceled).

Applicant: William R. Kissel
Serial No.: 10/828,756
Group Art Unit: 3682

40. (Canceled).